

Pending

Active

- ☞ L1: (5072) IMD or "intermodulation distortion"
- ☞ L2: (44) 1 and (suppress\$3 near8 IMD)
- ☞ L3: (33) 2 and RF
- ☞ L4: (4) 3 and UMTS
- ☞ L5: (1) 3 and "active channel"
- ☞ L6: (1) 3 and (scanning adj receiver)
- ☞ L7: (3) 3 and (active near2 channel)
- ☞ L8: (18) 3 and (frequency adj band)
- ☞ L9: (12) 3 and (frequency adj band)
- ☞ L10: (2) 9 and PLL
- ☞ L11: (35) (IMD or "intermodulation distortion") and UMTS
- ☞ L12: (33) 11 and (RF or "radio frequency")
- ☞ L13: (2) 12 and (portion near8 (frequency adj band))
- ☞ L14: (30) (tony near2 nguyen).xp.
- ☞ L15: (0) (thuan near2 nguyen).xp.
- ☞ L16: (237) (thuan near2 nguyen).xa.
- ☞ L17: (2) 13 and threshold
- ☞ L18: (1) 17 and "spectral distance"
- ☞ L19: (2) 11 and "spectral distance"
- ☞ L20: (2) 19 and (subtract\$3 or add\$3)

Failed

Saved

Favorites

Tagged (5)

Info List Browse Linear Clear

DBs: US-PG-PUB:USPAT:EPO

☒ Plurals

Default generator: OR

☒ Highlight all hit terms initially

19 and (subtract\$3 or add\$3)
























BRS form IS&amp;R form Image Text HTML

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current X	Ref	Inventor	S
1	<input type="checkbox"/>	<input type="checkbox"/>	US 20020146996 A1	20021010	14	Scanning receiver for use in power amplifier linearization	455/302	455/296		Bachman, Thomas A. II et al.	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6674324 B1	20040106	14	System and method for producing an amplified signal using plurality of amp	330/52	330/149; 330/151		Ocenasek, Josef et al.	<input checked="" type="checkbox"/>

Hits Details HTML

Ready

NUM

-  Drafts
-  Pending
-  Active
  -  L1: (5072) IMD or "intermodulation distortion"
  -  L2: (44) 1 and (suppress\$3 near8 IMD)
  -  L3: (33) 2 and RF
  -  L4: (4) 3 and UMTS
  -  L5: (1) 3 and "active channel"
  -  L6: (1) 3 and (scanning adj receiver)
  -  L7: (3) 3 and (active near2 channel)
  -  L8: (18) 3 and (frequency adj band)
  -  L9: (12) 3 and (frequency adj band)
  -  L10: (2) 9 and PLL
  -  L11: (35) (IMD or "intermodulation distortion") and UMTS
  -  L12: (33) 11 and (RF or "radio frequency")
  -  L13: (2) 12 and (portion near8 (frequency adj band))
-  Failed
-  Saved
-  Favorites
-  Tagged (5)
-  UDC
-  Queue
-  Trash

☒ Purals

Default operator: 
☒ Highlight all hit terms initially

12 and (portion near8 (frequency adj band))

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current X	Retri	Inventor	S
1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6829471 B2	20041207	14	Digital baseband receiver in a multi-carrier power amplifier	455/194.2	455/114.3; 455/202		White; Paul E. et al.	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6674324 B1	20040106	14	System and method for producing an amplified signal using plurality of amp	330/52	330/149; 330/151		Ocenasek; Josef et al.	<input checked="" type="checkbox"/>